info@nazolux.com
www.nazolux.com

MIDI PRO FLOOD

SKU: NZ-0001

Description:

-- Direct lighting luminaire for use with LEDs.
-- Housing made from Corrosion resistant die-cast aluminium raw material.
-- Installation with bracket on floor, walls and ceiling surfaces.
-- Installation on ground with extended spike adaptor.
-- Mains voltage: 220-240V / 50-60Hz.
-- Clever thermal design.
-- Superspot, spot, medium and flood beam angles available.
-- Led colour temperatures are optionally 2700K, 3000K, 3500K, 4000K,5000K and 6500K.
-- Internal silicon gaskets ensure IP protection.
-- All external screws are stainless steel.
-- Double layer polyester powder paint resistant to corrosion and salt spray fog.
-- Up to 94lm/W efficiency.
-- High colour consistency: <3 SDCM
-- Stainless steel cable gland and mains cable provided with IP68 socket and water stopper in the middle of the cable to avoid vapor enter inside the projector.
-- Mechanical aiming lock.
-- DALI and 1-10V dimming options available.
-- Due to high heatsink capacity, Nano can operate in high Ta teperature conditions.
-- L80 B10 50000hrs

-- Available angle beams: 6,10,33 dg

Technical Informations:

Model	Power	CRI	Kelvin	Lumen
MIDI PRO FLOOD	10w	CRI 70	2700K	837
			3000K	851
			3500K	890
			4000K	898
			5000K	919
			6500K	929
		CRI 80	2700K	828
			3000K	832
			3500K	870
			4000K	889
			5000K	898
			6500K	908